

TW10a

10" Two Way Full Range Active Speaker

DESCRIPTION

Portable and installed active loudspeakers used in applications including sound reinforcement in Front of House and Foldback applications in house of worship, events, clubs, rehearsal etc. Both active and passive version deliver extraordinary performance at unmatched value.



FEATURES

- High output SPL and sensitivity
- Built-in high power amplifier module with DSP
- Master volume control
- XLR input and output connectors
- Smart sound quality adjustment
- Integrated pole mount adaptor at bottom
- Portable system (stand), or permanent installation (wall, ceiling, under balcony)
- Suitable for use as a main system with or without sub speaker augmentation
- Powder coated protective grill
- Durable Polyurethane textured base paint

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	55Hz-19kHz
	Max SPL @ 1m:	112dB/118dB(PEAK)
	Dispersion (H x V):	80° x 70°
Transducers	Compression driver:	1 x 1.3" HF
	Woofer:	1 x 10" LF
Input/Output section	Input signal:	Balanced 20k Ω , Unbalanced 10k Ω
Power section	Total Power:	450W(RMS);
	Nominal Impedance (Ohm):	8 Ω
	Voltage range:	AC 220V-240V~, 50/60Hz (or AC 110V-120V~, 50/60Hz)
Physical specifications	Cabinet/Case Material:	Plywood
	Hardware:	1 x wall mounting bracket (optional), 1 x U bracket (optional)
	Handles:	2 x Wooden handles
	Grille:	Cabinet coated by Polyurethane paint; grille is powder coated
	Color:	Black
Size	Dimension (W x D x H):	335 x 335 x 530mm / (13.2 x 13.2 x 20.9in)
	Package Dimensions (W x D x H):	425 x 425 x 630mm / (16.7 x 16.7 x 24.8in)
Weight	Net Weight:	16.4 kg / 36.2 lb
	Gross Weight:	18.5 kg / 40.8 lb