

TW215a

Dual 15" Two Way Full Range Active Speaker

DESCRIPTION

Portable and installed active loudspeakers used in applications including sound reinforcement in Front of House and Foldback applications in house of worship, events, clubs, rehearsal etc. Both active and passive version deliver extraordinary performance at unmatched value.



FEATURES

- High output SPL and sensitivity
- Built-in high power amplifier module with DSP
- Master volume control
- XLR input and output connectors
- Smart sound quality adjustment
- Integrated pole mount adaptor at bottom
- Portable system (stand), or permanent installation (wall, ceiling, under balcony)
- Suitable for use as a main system with or without sub speaker augmentation
- Powder coated protective grill
- Durable Polyurethane textured base paint

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response(-3db):	45Hz-18kHz
	Max SPL @ 1m:	128dB/134dB(PEAK)
	Dispersion (H x V):	50° x 55°
Transducers	Compression driver:	1 x 3" HF
	Woofer:	2 x 15" LF
Input/Output section	Input signal:	Balanced 20k Ω , Unbalanced 2k Ω
	Input Connectors:	Input: 2 x Combo(one with Mic/Line switch), Output: 3 x XLR
Power section	Total Power:	1500W(RMS);
	Nominal Impedance (Ohm):	4 Ω
	Voltage range:	AC 220V-240V~, 50/60Hz (or AC 110V-120V~, 50/60Hz)
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Plywood
	Hardware:	11 x M10 hanging point
	Handles:	6 x Wooden handles
	Grille:	Cabinet coated by Polyurethane paint; grille is powder coated
	Color:	Black
Size	Dimension (W x D x H):	520 x 520 x 1090mm / (20.5 x 20.5 x 42.9in)
	Package Dimensions (W x D x H):	650 x 650 x 1240mm / (25.6 x 25.6 x 48.8in)
Weight	Net Weight:	53 kg / 116.8 lb
	Gross Weight:	60 kg / 132.3 lb